

## Grease Transfer

The Banlaw Grease Transfer Coupling is safe, fast, and easy-to-use.

Flush-faced design and a positive-connect feel mitigate the risk of common grease-related injuries.

The GTX also offers superior grease transfer rates when compared with competitor products.



Part Number	Product Description	Tech Specs	Shipping Specs	Items Included
GTXNB	Nozzle Flush Face Grease 3/4" NPTF	3/4" NPTF, CT	Dimensions - 12x7x7cm   Weight - 1.2kg	(blank)
GTXNB - CT	Nozzle Flush Face Grease 3/4" NPTF, Cold Temp	3/4" NPTF, CT	Dimensions - 12x7x7cm   Weight - 1.2kg	(blank)
GTXNC	Nozzle Flush Face Grease 1" NPTF	1" NPTF, CT	Dimensions - 12x7x7cm   Weight - 1.2kg	(blank)
GTXNC - CT	Nozzle Flush Face Grease 1" NPTF, Cold Temp	1" NPTF, CT	Dimensions - 12x7x7cm   Weight - 1.2kg	(blank)
GTXRA	Receiver Flush Face Grease 1/2" NPTM	1/2" NPTM	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap
GTXRA - CT	Receiver Flush Face Grease 1/2" NPTM, Cold Temp	1/2" NPTM, CT	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap
GTXRB	Receiver Flush Face Grease 3/4" NPTM	3/4" NPTM	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap
GTXRB - CT	Receiver Flush Face Grease 3/4" NPTM, Cold Temp	3/4" NPTM, CT	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap
GTXRBO	Receiver Flush Face Grease 3/4" UNOM	3/4" UNOM	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap
GTXRBO - CT	Receiver Flush Face Grease 3/4" UNOM, Cold Temp	3/4" UNOM, CT	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap
GTXRC	Receiver Flush Face Grease 1" NPTM	1" NPTM	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap
GTXRC - CT	Receiver Flush Face Grease 1" NPTM, Cold Temp	1" NPTM, CT	Dimensions - 10x6x6cm   Weight - 0.6kg	Receiver and Cap