

AIR OPERATED OIL PUMPS (T-SERIES)

Non-corroding & lubrication free

Innovative design with the use of polymer materials in the air motor

Low air consumption

Smaller compressor and cost efficient to run

Durable yet lightweight design

Thermal plastic material with heavy duty construction



Underground mining capability

Zinc versions available suitable for underground mining



OILMASTER® T-SERIES AIR OPERATED OIL PUMPS

The OILMASTER® T-Series stub and drum oil pumps are premium quality, reliable, economically priced oil transfer pumps.

With no need for air line lubrication and a low air consumption design, this robust yet lightweight range of air operated stub and drum pumps are perfect for small to medium workshop and mobile installations.

TECHNICAL SPECIFICATIONS

- Min/Max air pressure: 400 – 1030kPa (60/150psi)
- Compatible fluids: engine and gear oils up to SAE 140, auto trans, hydraulic fluid and anti-freeze/anti-boil
- Supplied with 2" bung adaptor only
- Air line lubricator not required
- Available in both stub or drum types

Recommended to be used with:



TD20-BLACKS:

Wall bracket



HG Series gun:

Oil control guns



TB25S:

Telescopic suction tube



OMP2121 :

RETRACTA® oil reel suitable for 3:1 pumps



OMP2101:

RETRACTA® oil reel suitable for 5:1 pumps

AIR OPERATED OIL PUMPS

OILMASTER® 1:1 AIR OPERATED STUB PUMP T112S-01



TECHNICAL SPECIFICATIONS

- 1:1 Ratio pump
- Free flow delivery up to 23LPM (approx. 10m distance)
- 1" BSP (F) fluid inlet / 3/4" BSP (F) fluid outlet
- Suitable for oils & coolants up to SAE 90 viscosity
- Min air compressor: 0.3m³/min (10 cfm)
- **T112T-01:** OILMASTER® 1:1 air operated drum pump

REPAIR KITS

- **T112-1K:** Overhaul Kit
- **ST003AS:** Suction Tube Set

OILMASTER® 3:1 AIR OPERATED STUB PUMP T312S-01



TECHNICAL SPECIFICATIONS

- 3:1 Ratio pump
- Free flow delivery up to 13LPM (approx. 30m distance)
- 1" BSP (F) fluid inlet / 3/4" BSP (F) fluid outlet
- Suitable for oils & coolants up to SAE 140 viscosity
- Built-in pressure relief valve
- Min air compressor: 0.3m³/min (10 cfm)
- **T312T-01:** OILMASTER® 1:1 air operated drum pump

REPAIR KITS

- **T312-1K:** Overhaul Kit
- **ST003AS:** Suction Tube Set

OILMASTER® 5:1 AIR OPERATED STUB PUMP T512S-01



TECHNICAL SPECIFICATIONS

- 5:1 Ratio pump
- Free flow delivery up to 11LPM (approx. 50m distance)
- 1" BSP (F) fluid inlet / 1/2" BSP (F) fluid outlet
- Suitable for oils & coolants up to SAE 140 viscosity
- Built-in pressure relief valve
- Min air compressor: 0.15m³/min (5 cfm)
- **T512T-01:** OILMASTER® 1:1 air operated drum pump
- **T512-01-11:** OILMASTER® 1:1 air operated stub pump for underground mining

REPAIR KITS

- **T512-1K:** Overhaul Kit
- **ST003AS:** Suction Tube Set